

双向推力圆锥滚子轴承



Main dimensions(mm)							Basic load ratings(kN)		Fatigue load limit	Weight	Design
d	D	H	r 1.2min	r 3.4min	ra max	rb max	Cr	Cor	□Cu□	(kg)	
170	240	84	0,6	2	0,6	2	325,00	1300	103	12,5	350980
180	280	90	1	2	1	2	560,0	2350	197	22	353162
220	300	96	0,6	2	0,6	2	435,0	1650	133	20	351019
240	320	96	0,6	2	0,6	2	420,0	1880	145	21,5	351182
250	380	100	0,6	2	0,6	2	910,0	4500	340	43,5	353005
260	360	92	1	2	1	2	600,0	2650	190	28	350981
270	450	180	2	5	2	4	1645	5900	460	120	351164
305,07	530	200	6,4	6,4	6	6	2395,0	10500	685	185	353194
320	440	108	1,1	3	1	2,5	1000,0	4900	340	48,5	353102
	470	130	1,1	3	1	2,5	1320,0	5650	410	80	350982
350	490	130	1,1	3	1	2,5	1150,0	5100	345	73,5	351100
	540	135	1,1	4	1	3	1700	9100	625	115	353006
380	560	130	1,5	3	1,5	2,5	1800,0	9900	675	110	351175
	650	215	2	4	2	3	3350,0	16300	1080	275	353204
400	650	200	4	4	4	4	2750,0	13500	825	235	353106
420	620	170	1,5	3	1,5	3	2400,0	12100	805	185	351121
	620	185	1,5	3	1,5	3	2400,0	12120	805	200	353200
440	645	167	3	4	2,5	3	1950,0	10640	705	190	353152
450	645	155	4	4	3	3	1950,0	10900	690	170	350916
470	720	200	2	4	2	3	3350,0	17540	1100	285	353151
	720	200	2	4	2	3	3450,0	17540	1100	285	351301
	720	210	2	4	2	3	3400,0	17540	1100	305	353238
530	710	218	2	3	2	2,5	2170,0	10890	700	245	351475

双向推力圆锥滚子轴承

550	760	230	2	5	2	4	2950	13100	835	310	350976
600	880	290	5	6	4	5	4750	20940	1280	550	350824
	910	290	5	6	4	5	4750,0	21110	1280	655	350901
670	900	230	2	5	2	4	3550	18640	1140	425	351761